

Declaration of Performance
(according to Regulation EU No 305/2011)

No. AMOL-2/01-CPR-13-1

1) Code of the product type: **S235JR**

According to EN 10025-2

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

2) ArcelorMittal Gipuzkoa, S.L.U.
Fábrica de Olaberria
Carretera Madrid - Irún, Km. 417
20212 – Olaberria (Guipúzcoa – España)
T +34 943 805 000
sections.arcelormittal.com

System of assessment and verification of constancy of performance of the product:
System 2+

Notified factory production control certification body No. 0099 AENOR performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in point 1 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2. Signed for and on behalf of the manufacturer by:

Jose María Galindo
Quality and Technical Customer
Service Manager



Date : 03.05.2017

Essential characteristic		Performance		Harmonised technical specification	
Tolerances on dimensions and shape	I and H sections		EN 10034		EN 10025-1:2004
	Tapered Flange I		EN 10024		
	UPE, UPN		EN 10279		
Yield strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min		
		16	235		
	16	40	225		
	40	63	215		
	63	80			
	80	100			
100	140	195			
Tensile strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min	max	
	≤3	100	360	510	
	100	140	350	500	
Elongation	Nominal thickness (mm)		Values (%)		
	>	≤	min		
	≤3	40	26		
	40	63	25		
	63	100	24		
	100	140	22		
Impact strength	Nominal thickness (mm)		Values (J)		
	>	≤	min		
		140	27 at +20°C		
Weldability	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		30	0,35		
	30	40	0,35		
40	140	0,38			
Durability (Chemical composition)	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		140	C* : 0,17 Mn : 1,40 P : 0,040	Cu : 0,55 S : 0,040 N** : 0,012	
<small>* For nominal thickness > 40 mm C: 0,20. For nominal thickness >100 mm: C content upon agreement ** The max. value for nitrogen does not apply if the chemical composition shows a minimum total Al content of 0,020% or if sufficient other N binding elements are present</small>					

Declaration of Performance
(according to Regulation EU No 305/2011)

No. AMOL-2/02-CPR-13-1

1) Code of the product type: **S235J0**

According to EN 10025-2

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

2) ArcelorMittal Gipuzkoa, S.L.U.
Fábrica de Olaberria
Carretera Madrid - Irún, Km. 417
20212 – Olaberria (Guipúzcoa – España)
T +34 943 805 000
sections.arcelormittal.com

System of assessment and verification of constancy of performance of the product:
System 2+

Notified factory production control certification body No. 0099 AENOR performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in point 1 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2. Signed for and on behalf of the manufacturer by:

Jose María Galindo
Quality and Technical Customer
Service Manager



Date : 03.05.2017

Essential characteristic		Performance		Harmonised technical specification	
Tolerances on dimensions and shape	I and H sections		EN 10034		EN 10025-1:2004
	Tapered Flange I		EN 10024		
	UPE, UPN		EN 10279		
Yield strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min		
		16	235		
	16	40	225		
	40	63	215		
	63	80			
	80	100			
100	140	195			
Tensile strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min	max	
	≤3	100	360	510	
	100	140	350	500	
Elongation	Nominal thickness (mm)		Values (%)		
	>	≤	min		
	≤3	40	26		
	40	63	25		
	63	100	24		
	100	140	22		
Impact strength	Nominal thickness (mm)		Values (J)		
	>	≤	min		
		140	27 at 0°C		
Weldability	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		30	0,35		
	30	40	0,35		
40	140	0,38			
Durability (Chemical composition)	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		140	C* : 0,17	Cu : 0,55	
			Mn : 1,40	S : 0,035	
		P : 0,035	N** : 0,012		
* For nominal thickness >100 mm: C content upon agreement.					
** The max. value for nitrogen does not apply if the chemical composition shows a minimum total Al content of 0,020% or if sufficient other N binding elements are present					



Declaration of Performance
(according to Regulation EU No 305/2011)

No. AMOL-2/03-CPR-13-1

1) Code of the product type: **S235J2**

According to EN 10025-2

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

2) ArcelorMittal Gipuzkoa, S.L.U.
Fábrica de Olaberria
Carretera Madrid - Irún, Km. 417
20212 – Olaberria (Guipúzcoa – España)
T +34 943 805 000
sections.arcelormittal.com

System of assessment and verification of constancy of performance of the product:
System 2+

Notified factory production control certification body No. 0099 AENOR performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in point 1 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2. Signed for and on behalf of the manufacturer by:

Jose María Galindo
Quality and Technical Customer
Service Manager

Date : 03.05.2017

Essential characteristic		Performance		Harmonised technical specification	
Tolerances on dimensions and shape	I and H sections		EN 10034		EN 10025-1:2004
	Tapered Flange I		EN 10024		
	UPE, UPN		EN 10279		
Yield strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min		
		16	235		
	16	40	225		
	40	63	215		
	63	80			
	80	100			
100	140	195			
Tensile strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min	max	
	≤3	100	360	510	
	100	140	350	500	
Elongation	Nominal thickness (mm)		Values (%)		
	>	≤	min		
	≤3	40	26		
	40	63	25		
	63	100	24		
	100	140	22		
Impact strength	Nominal thickness (mm)		Values (J)		
	>	≤	min		
		140	27 at -20°C		
Weldability	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		30	0,35		
	30	40	0,35		
40	140	0,38			
Durability (Chemical composition)	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		140	C* : 0,17 Mn : 1,40 P : 0,030	Cu : 0,55 S : 0,030	
* For nominal thickness >100 mm: C content upon agreement. Fully killed steel containing nitrogen binding element in amounts sufficient to bind the available nitrogen (for example min. 0,02% Al)					

Declaration of Performance
(according to Regulation EU No 305/2011)

No. AMOL-2/04-CPR-13-1

1) Code of the product type: **S275JR**

According to EN 10025-2

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

2) ArcelorMittal Gipuzkoa, S.L.U.
Fábrica de Olaberria
Carretera Madrid - Irún, Km. 417
20212 – Olaberria (Guipúzcoa – España)
T +34 943 805 000
sections.arcelormittal.com

System of assessment and verification of constancy of performance of the product:
System 2+

Notified factory production control certification body No. 0099 AENOR performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in point 1 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2. Signed for and on behalf of the manufacturer by:

Jose María Galindo
Quality and Technical Customer
Service Manager



Date : 03.05.2017

Essential characteristic		Performance		Harmonised technical specification	
Tolerances on dimensions and shape	I and H sections		EN 10034		EN 10025-1:2004
	Tapered Flange I		EN 10024		
	UPE, UPN		EN 10279		
Yield strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min		
		16	275		
	16	40	265		
	40	63	255		
	63	80	245		
	80	100	235		
100	140	225			
Tensile strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min	max	
	≤3	100	410	560	
	100	140	400	540	
Elongation	Nominal thickness (mm)		Values (%)		
	>	≤	min		
	≤3	40	23		
	40	63	22		
	63	100	21		
	100	140	19		
Impact strength	Nominal thickness (mm)		Values (J)		
	>	≤	min		
		140	27 at +20°C		
Weldability	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		30	0,40		
	30	40	0,40		
40	140	0,42			
Durability (Chemical composition)	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		140	C* : 0,21 Mn : 1,50 P : 0,040	Cu : 0,55 S : 0,040 N** : 0,012	
* For nominal thickness > 40 mm C: 0,22. For nominal thickness >100 mm: C content upon agreement					
** The max. value for nitrogen does not apply if the chemical composition shows a minimum total Al content of 0,020% or if sufficient other N binding elements are present					

Declaration of Performance
(according to Regulation EU No 305/2011)

No. AMOL-2/05-CPR-13-1

1) Code of the product type: **S275J0**

According to EN 10025-2

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

2) ArcelorMittal Gipuzkoa, S.L.U.
Fábrica de Olaberria
Carretera Madrid - Irún, Km. 417
20212 – Olaberria (Guipúzcoa – España)
T +34 943 805 000
sections.arcelormittal.com

System of assessment and verification of constancy of performance of the product:
System 2+

Notified factory production control certification body No. 0099 AENOR performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in point 1 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2. Signed for and on behalf of the manufacturer by:

Jose María Galindo
Quality and Technical Customer
Service Manager



Date : 03.05.2017

Essential characteristic		Performance		Harmonised technical specification	
Tolerances on dimensions and shape	I and H sections		EN 10034		EN 10025-1:2004
	Tapered Flange I		EN 10024		
	UPE, UPN		EN 10279		
Yield strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min		
		16	275		
	16	40	265		
	40	63	255		
	63	80	245		
	80	100	235		
Tensile strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min	max	
	≤3	100	410	560	
	100	140	400	540	
Elongation	Nominal thickness (mm)		Values (%)		
	>	≤	min		
	≤3	40	23		
	40	63	22		
	63	100	21		
	100	140	19		
Impact strength	Nominal thickness (mm)		Values (J)		
	>	≤	min		
		140	27 at 0°C		
Weldability	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		30	0,40		
	30	40	0,40		
Durability (Chemical composition)	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		140	C* : 0,18	Cu : 0,55	
			Mn : 1,50	S : 0,035	
			P : 0,035	N** : 0,012	
* For nominal thickness >100 mm: C content upon agreement.					
** The max. value for nitrogen does not apply if the chemical composition shows a minimum total Al content of 0,020% or if sufficient other N binding elements are present					



Declaration of Performance
(according to Regulation EU No 305/2011)

No. AMOL-2/06-CPR-13-1

1) Code of the product type: **S275J2**

According to EN 10025-2

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

2) ArcelorMittal Gipuzkoa, S.L.U.
Fábrica de Olaberria
Carretera Madrid - Irún, Km. 417
20212 – Olaberria (Guipúzcoa – España)
T +34 943 805 000
sections.arcelormittal.com

System of assessment and verification of constancy of performance of the product:
System 2+

Notified factory production control certification body No. 0099 AENOR performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in point 1 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2. Signed for and on behalf of the manufacturer by:

Jose María Galindo
Quality and Technical Customer
Service Manager

Date : 03.05.2017

Essential characteristic		Performance		Harmonised technical specification	
Tolerances on dimensions and shape	I and H sections		EN 10034		EN 10025-1:2004
	Tapered Flange I		EN 10024		
	UPE, UPN		EN 10279		
Yield strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min		
		16	275		
	16	40	265		
	40	63	255		
	63	80	245		
	80	100	235		
Tensile strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min	max	
	≠3	100	410	560	
	100	140	400	540	
Elongation	Nominal thickness (mm)		Values (%)		
	>	≤	min		
	≠3	40	23		
	40	63	22		
	63	100	21		
	100	140	19		
Impact strength	Nominal thickness (mm)		Values (J)		
	>	≤	min		
		140	27 at -20°C		
Weldability	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		30	0,40		
	30	40	0,40		
Durability (Chemical composition)	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		140	C* : 0,18	Cu : 0,55	
			Mn : 1,50	S : 0,030	
		P : 0,030			
* For nominal thickness >100 mm: C content upon agreement. Fully killed steel containing nitrogen binding element in amounts sufficient to bind the available nitrogen (for example min. 0,02% Al)					

Declaration of Performance
(according to Regulation EU No 305/2011)

No. AMOL-2/07-CPR-13-1

1) Code of the product type: **S355JR**

According to EN 10025-2

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

2) ArcelorMittal Gipuzkoa, S.L.U.
Fábrica de Olaberria
Carretera Madrid - Irún, Km. 417
20212 – Olaberria (Guipúzcoa – España)
T +34 943 805 000
sections.arcelormittal.com

System of assessment and verification of constancy of performance of the product:
System 2+

Notified factory production control certification body No. 0099 AENOR performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in point 1 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2. Signed for and on behalf of the manufacturer by:

Jose María Galindo
Quality and Technical Customer
Service Manager



Date : 03.05.2017

Essential characteristic		Performance		Harmonised technical specification	
Tolerances on dimensions and shape	I and H sections		EN 10034		EN 10025-1:2004
	Tapered Flange I		EN 10024		
	UPE, UPN		EN 10279		
Yield strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min		
		16	355		
	16	40	345		
	40	63	335		
	63	80	325		
	80	100	315		
100	140	295			
Tensile strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min	max	
	≤3	100	470	630	
	100	140	450	600	
Elongation	Nominal thickness (mm)		Values (%)		
	>	≤	min		
	≤3	40	22		
	40	63	21		
	63	100	20		
	100	140	18		
Impact strength	Nominal thickness (mm)		Values (J)		
	>	≤	min		
		140	27 at +20°C		
Weldability	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		30	0,45		
	30	40	0,47		
40	140	0,47			
Durability (Chemical composition)	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		140	C* : 0,24 Si : 0,55 Mn : 1,60 P : 0,040	Cu : 0,55 S : 0,040 N** : 0,012	
* For nominal thickness >100 mm: C content upon agreement.					
** The max. value for nitrogen does not apply if the chemical composition shows a minimum total Al content of 0,020% or if sufficient other N binding elements are present					

Declaration of Performance
(according to Regulation EU No 305/2011)

No. AMOL-2/08-CPR-13-1

1) Code of the product type: **S355J0**

According to EN 10025-2

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

2) ArcelorMittal Gipuzkoa, S.L.U.
Fábrica de Olaberria
Carretera Madrid - Irún, Km. 417
20212 – Olaberria (Guipúzcoa – España)
T +34 943 805 000
sections.arcelormittal.com

System of assessment and verification of constancy of performance of the product:
System 2+

Notified factory production control certification body No. 0099 AENOR performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in point 1 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2. Signed for and on behalf of the manufacturer by:

Jose María Galindo
Quality and Technical Customer
Service Manager



Date : 03.05.2017

Essential characteristic		Performance		Harmonised technical specification	
Tolerances on dimensions and shape	I and H sections		EN 10034		EN 10025-1:2004
	Tapered Flange I		EN 10024		
	UPE, UPN		EN 10279		
Yield strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min		
		16	355		
	16	40	345		
	40	63	335		
	63	80	325		
	80	100	315		
Tensile strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min	max	
	≤3	100	470	630	
	100	140	450	600	
Elongation	Nominal thickness (mm)		Values (%)		
	>	≤	min		
	≤3	40	22		
	40	63	21		
	63	100	20		
	100	140	18		
Impact strength	Nominal thickness (mm)		Values (J)		
	>	≤	min		
		140	27 at 0°C		
Weldability	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		30	0,45		
	30	40	0,47		
	40	140	0,47		
Durability (Chemical composition)	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		140	C* : 0,20	Cu : 0,55	
			Si : 0,55	S : 0,035	
		Mn : 1,60	N** : 0,012		
		P : 0,035			
* For nominal thickness > 30 mm C: 0,22. For nominal thickness >100 mm: C content upon agreement					
** The max. value for nitrogen does not apply if the chemical composition shows a minimum total Al content of 0,020% or if sufficient other N binding elements are present					

Declaration of Performance
(according to Regulation EU No 305/2011)

No. AMOL-2/09-CPR-13-1

1) Code of the product type: **S355J2**

According to EN 10025-2

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

2) ArcelorMittal Gipuzkoa, S.L.U.
Fábrica de Olaberria
Carretera Madrid - Irún, Km. 417
20212 – Olaberria (Guipúzcoa – España)
T +34 943 805 000
sections.arcelormittal.com

System of assessment and verification of constancy of performance of the product:
System 2+

Notified factory production control certification body No. 0099 AENOR performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in point 1 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2. Signed for and on behalf of the manufacturer by:

Jose María Galindo
Quality and Technical Customer
Service Manager



Date : 03.05.2017

Essential characteristic		Performance		Harmonised technical specification	
Tolerances on dimensions and shape	I and H sections		EN 10034		EN 10025-1:2004
	Tapered Flange I		EN 10024		
	UPE, UPN		EN 10279		
Yield strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min		
		16	355		
	16	40	345		
	40	63	335		
	63	80	325		
	80	100	315		
100	140	295			
Tensile strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min	max	
	≤3	100	470	630	
	100	140	450	600	
Elongation	Nominal thickness (mm)		Values (%)		
	>	≤	min		
	≤3	40	22		
	40	63	21		
	63	100	20		
	100	140	18		
Impact strength	Nominal thickness (mm)		Values (J)		
	>	≤	min		
		140	27 at -20°C		
Weldability	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		30	0,45		
	30	40	0,47		
40	140	0,47			
Durability (Chemical composition)	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		140	C* : 0,20 Si : 0,55 Mn : 1,60	Cu : 0,55 S : 0,030 P : 0,030	
* For nominal thickness > 30 mm C: 0,22. For nominal thickness >100 mm: C content upon agreement Fully killed steel containing nitrogen binding element in amounts sufficient to bind the available nitrogen (for example min. 0,02% Al)					



Declaration of Performance
(according to Regulation EU No 305/2011)

No. AMOL-2/10-CPR-13-1

1) Code of the product type: **S355K2**

According to EN 10025-2

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

2) ArcelorMittal Gipuzkoa, S.L.U.
Fábrica de Olaberria
Carretera Madrid - Irún, Km. 417
20212 – Olaberria (Guipúzcoa – España)
T +34 943 805 000
sections.arcelormittal.com

System of assessment and verification of constancy of performance of the product:
System 2+

Notified factory production control certification body No. 0099 AENOR performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in point 1 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2. Signed for and on behalf of the manufacturer by:

Jose María Galindo
Quality and Technical Customer
Service Manager

Date : 03.05.2017

Essential characteristic		Performance		Harmonised technical specification	
Tolerances on dimensions and shape	I and H sections		EN 10034		EN 10025-1:2004
	Tapered Flange I		EN 10024		
	UPE, UPN		EN 10279		
Yield strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min		
		16	355		
	16	40	345		
	40	63	335		
	63	80	325		
	80	100	315		
100	140	295			
Tensile strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min	max	
	≤3	100	470	630	
	100	140	450	600	
Elongation	Nominal thickness (mm)		Values (%)		
	>	≤	min		
	≤3	40	22		
	40	63	21		
	63	100	20		
	100	140	18		
Impact strength	Nominal thickness (mm)		Values (J)		
	>	≤	min		
		140	40 at -20°C		
Weldability	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		30	0,45		
	30	40	0,47		
40	140	0,47			
Durability (Chemical composition)	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		140	C* : 0,20 Si : 0,55 Mn : 1,60	Cu : 0,55 S : 0,030 P : 0,030	
* For nominal thickness > 30 mm C: 0,22. For nominal thickness >100 mm: C content upon agreement Fully killed steel containing nitrogen binding element in amounts sufficient to bind the available nitrogen (for example min. 0,02% Al)					

Declaration of Performance
(according to Regulation EU No 305/2011)

No. AMOL-5/01-CPR-13-1

1) Code of the product type: **S355J0W**

According to EN 10025-5

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

2) ArcelorMittal Gipuzkoa, S.L.U.
Fábrica de Olaberria
Carretera Madrid - Irún, Km. 417
20212 – Olaberria (Guipúzcoa – España)
T +34 943 805 000
sections.arcelormittal.com

System of assessment and verification of constancy of performance of the product:
System 2+

Notified factory production control certification body No. 0099 AENOR performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in point 1 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2. Signed for and on behalf of the manufacturer by:

Jose María Galindo
Quality and Technical Customer
Service Manager



Date : 03.05.2017

Essential characteristic		Performance		Harmonised technical specification	
Tolerances on dimensions and shape	I and H sections		EN 10034		EN 10025-1:2004
	Tapered Flange I		EN 10024		
	UPE, UPN		EN 10279		
Yield strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min		
		16	355		
	16	40	345		
Tensile strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min	max	
	≠3	40	470	630	
Elongation	Nominal thickness (mm)		Values (%)		
	>	≤	min		
	≠3	40	22		
Impact strength	Nominal thickness (mm)		Values (J)		
	>	≤	min		
		40	27 at 0°C		
Weldability	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		16	0,52		
	16	40	0,52		
Durability (Chemical composition)	Nominal thickness (mm)		Values (%)		
	>	≤	min	max	
		40		C : 0,16 S : 0,040 Si : 0,50 N* : 0,009 P : 0,040	
			Mn : 0,50 Cu : 0,25 Cr : 0,40	Mn : 1,50 Cu : 0,55 Cr : 0,80	
	* It is permissible to exceed the specified values provided that for each increase of 0,001 % N, the Pmax content will be reduced by 0,005%; the N content of the ladle analysis, however, shall not be more than 0,012%. The max. value for nitrogen does not apply if the chemical composition shows a minimum total Al content of 0,020% or if sufficient other N binding elements are present. The N binding elements shall be mentioned in the inspection document.				
The steels may show a Ni content of max. 0,65%. The steels may contain max. 0,30% Mo and max. 0,15% Zr.					



Declaration of Performance
(according to Regulation EU No 305/2011)

No. AMOL-5/02-CPR-13-1

1) Code of the product type: **S355J2W**

According to EN 10025-5

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

To be used in welded, bolted and riveted structures

2) ArcelorMittal Gipuzkoa, S.L.U.
Fábrica de Olaberria
Carretera Madrid - Irún, Km. 417
20212 – Olaberria (Guipúzcoa – España)
T +34 943 805 000
sections.arcelormittal.com

System of assessment and verification of constancy of performance of the product:
System 2+

Notified factory production control certification body No. 0099 AENOR performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment, and evaluation of factory production control and issued the certificate of conformity of the factory production control.

The performance of the product identified in point 1 is in conformity with the declared performance in the table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 2. Signed for and on behalf of the manufacturer by:

Jose María Galindo
Quality and Technical Customer
Service Manager

Date : 03.05.2017

Essential characteristic		Performance		Harmonised technical specification	
Tolerances on dimensions and shape	I and H sections		EN 10034		EN 10025-1:2004
	Tapered Flange I		EN 10024		
	UPE, UPN		EN 10279		
Yield strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min		
		16	355		
	16	40	345		
Tensile strength	Nominal thickness (mm)		Values (MPa)		
	>	≤	min	max	
	≠3	40	470	630	
Elongation	Nominal thickness (mm)		Values (%)		
	>	≤	min		
	≠3	40	22		
Impact strength	Nominal thickness (mm)		Values (J)		
	>	≤	min		
		40	27 at -20°C		
Weldability	Nominal thickness (mm)		Values (%)		
	>	≤	max		
		16	0,52		
	16	40	0,52		
Durability (Chemical composition)	Nominal thickness (mm)		Values (%)		
	>	≤	min	max	
		40		C : 0,16 S : 0,035 Si : 0,50 N* : 0,009 P : 0,035	
			Mn : 0,50 Cu : 0,25 Cr : 0,40	Mn : 1,50 Cu : 0,55 Cr : 0,80	
* It is permissible to exceed the specified values provided that for each increase of 0,001 % N, the P _{max} content will be reduced by 0,005%; the N content of the ladle analysis, however, shall not be more than 0,012%. The max. value for nitrogen does not apply if the chemical composition shows a minimum total Al content of 0,020% or if sufficient other N binding elements are present.					
Addition of nitrogen binding elements: the steels shall contain at least one of the following elements: Al total ≥ 0,020%, Nb: 0,015 - 0,060%, V: 0,02-0,12%, Ti: 0,02 - 0,10%. If these elements are used in combination, at least one of them shall be present with the minimum content indicated.					
The steels may show a Ni content of max. 0,65%. The steels may contain max. 0,30% Mo and max. 0,15% Zr.					
Fully killed steel containing nitrogen binding element in amounts sufficient to bind the available nitrogen (for example min. 0,02% Al)					